



** Protection from specific strains of bacterias*

ARMSTRONG BIOGUARD[®] PLAIN RH99

BENEFITS

- Anti-microbial & anti-mold performance to assist with infection control*
- Appealing smooth surface
- Water repellency & washable surface, ceiling tiles can be directly cleaned with wet cloth
- Resistance to growth of mould

APPLICATION AREAS

- Healthcare (Severe Risk Zones)
 - ICU
 - Small surgery areas
 - Radiology
 - Delivery Rooms
 - Laboratories
- Kitchens, food service & processing areas

ARMSTRONG BIOGUARD® PLAIN RH99

		Board	Tegular 24	Tegular 15 BE
Edge Details		 Prelude 24 mm	 Prelude 24 mm	 Suprafine 15 mm / Silhouette
Thickness (mm)		 16mm	 5mm 8mm 16mm 15°	 4.5mm 8mm 16mm
Dimensions(mm) Tiles		W5181 W5182	W5183 W5180	W5184 W5185
Weight		≅ 3.6 kgs/m ²		
Colour		White		
Sound attenuation		CAC = 35 dB		
Fire reaction		Class 0/ Class 1 as per BS 476 Pt - 6 & 7 Class A as per ASTM E-84		
Light reflectance		90%		
Thermal conductivity		$\lambda = 0.052 - 0.057 \text{ W/mK}$		
Humidity resistance		RH 99%		
Recycled content		Up to 34%		
Clean room classification		ISO 5 (Class 100)		
Cleanability		Wipeable with dry cloth		
		Wipeable with moist cloth		
Sustainability				
Contact us	Knauf Ceiling Solutions (India) Private Limited Boomerang, A-304, Chandivali Farm Road (near Chandivali Studio) Andheri (E), Mumbai - 400 072. Contact us: 1860 266 7080 e-mail : Helpdeskindia@knaufarmstrong.com			