



ULTIMA OP

BENEFITS

- Bright and elegant visual
- High sound absorption
- Easy handling & installation
- Clean Room Classification: Class 4

APPLICATION AREAS

- Offices
- Education Institutes
- Libraries
- Cinemas

	Board	Tegular 24/90	Tegular 15/90														
Edge Details	 Prelude 24 mm	 Prelude 24 mm	 Suprafine 15 mm / Silhouette														
Thickness (mm)	 19mm	 5mm / 8mm / 19mm	 4.5mm / 8mm / 19mm														
Dimensions(mm) 600 x 600 x 19 mm 1200 x 600 x 19 mm	BP1130I BP1131I	BP1132I BP1133I	BP1134I BP1135I														
Weight	≅ 3.3 kgs/m ²																
Colour	White																
Sound absorption	NRC = 0.90		 <table border="1"> <thead> <tr> <th>Frequency f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000 Hz</th> </tr> </thead> <tbody> <tr> <td>Partical sound</td> <td>0.50</td> <td>0.80</td> <td>0.90</td> <td>1.00</td> <td>1.00</td> <td>1.00</td> </tr> </tbody> </table>	Frequency f (Hz)	125	250	500	1000	2000	4000 Hz	Partical sound	0.50	0.80	0.90	1.00	1.00	1.00
Frequency f (Hz)	125	250		500	1000	2000	4000 Hz										
Partical sound	0.50	0.80	0.90	1.00	1.00	1.00											
Tiles <input checked="" type="checkbox"/>																	
Sound attenuation	CAC = 29 dB																
Fire reaction	A2-s1, d0 as per EN 13501-1																
Light reflectance	88%																
Thermal conductivity	$\lambda = 0.040 \text{ W/mK}$																
Humidity resistance	RH 99%																
Recycled content	Up to 43%																
Clean room classification	Class 4																
Environmental Product Declaration	As per ISO 14025 and EN 15804+A2																
Cleanability	Wipeable with dry cloth																
	Wipeable with moist cloth																
Sustainability	 																
Contact us	Knauf Ceiling Solutions (India) Private Limited Boomerang, A-304, Chandivali Farm Road (near Chandivali Studio) Andheri (E), Mumbai - 400 072. Contact us: 1860 266 7080 e-mail : Helpdeskindia@knaufarmstrong.com																