



ARMSTRONG CASA MAX 19

BENEFITS

- Pin hole visual
- High sound absorption: 0.70 NRC

APPLICATION AREAS

- Offices / Call Centre
- Healthcare
- Education
- Conference Rooms
- Auditoriums
- Corridors / Lobbies
- Libraries

	Board	Tegular 24	Tegular 15 BE														
Edge Details	 Prelude 24 mm	 Prelude 24 mm	 Suprafine 15 mm / Silhouette														
Thickness (mm)	 19mm	 5mm 8mm 15° 19mm	 4.5mm 8mm 19mm														
Dimensions(mm) Tiles 600 x 600 x 19 mm 600 x 1200 x 19 mm	BP69631 BP69641	BP69651 BP69661	BP69671 BP69681														
Weight	≅ 5.7 kgs/m ²																
Colour	White																
Sound absorption Tiles •	NRC = 0.70		 <table border="1"> <thead> <tr> <th>Frequency f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000 Hz</th> </tr> </thead> <tbody> <tr> <td>Partical sound</td> <td>• 0.45</td> <td>0.50</td> <td>0.60</td> <td>0.80</td> <td>0.75</td> <td>0.50 α_p</td> </tr> </tbody> </table>	Frequency f (Hz)	125	250	500	1000	2000	4000 Hz	Partical sound	• 0.45	0.50	0.60	0.80	0.75	0.50 α _p
Frequency f (Hz)	125	250		500	1000	2000	4000 Hz										
Partical sound	• 0.45	0.50	0.60	0.80	0.75	0.50 α _p											
Sound attenuation	CAC = 39 dB																
Fire reaction	A2-s1, d0 as per EN 13501-1																
Light reflectance	88%																
Thermal conductivity	λ = 0.060 W/mK																
Humidity resistance	RH 99%																
Recycled content	43%																
VOC Emissions (French)	A+																
Environmental Product Declaration	As per ISO 14025 and EN 15804+A2																
Cleanability	Wipeable with dry cloth																
	Wipeable with moist cloth																
Sustainability	 																
Contact us	Knauf Ceiling Solutions (India) Private Limited Boomerang, A-304, Chandivali Farm Road (near Chandivali Studio) Andheri (E), Mumbai - 400 072. Contact us: 1860 266 7080 e-mail : Helpdeskindia@knaufarmstrong.com																