



Perfect sound

**The first non-
fleece-laminated
class A absorber**

OWAlifetime collection




OWA

Multi Alpha

Multi Alpha is an all-rounder: fire protection, sound absorption, moisture resistance etc. Convince yourself of the wet-felt-quality and the price and performance of the first non-fleece-laminated class A absorber.



Multi Alpha

Material	Mineral tile
Reaction to fire	A2-s1,d0 in accordance with EN 13501-1
Colour	White
Thickness	15 mm nom.
Light reflexion	Approx. 88 (ISO 7724-2, ISO 7724-3)
Sound reduction*	$D_{n,t,w} = 30 \text{ dB to } 48 \text{ dB, CAC } 32 \text{ dB}$
Sound absorption	 $\alpha_w = 0.90 \mid \text{NRC} = 0.90$
Moisture resistance	 up to 95 % RH
Resistance to fire*	 up to REI 30 (EN 13501-2)

* dependent on system, soffit and other project specific factors



Module sizes in mm	exposed	
	S 3	S 3 cliq
600 x 600	▪	▪
610 x 610	▪	▪
625 x 625	▪	▪
1200 x 600	▪	▪
1220 x 610	▪	▪
1250 x 625	▪	▪



Odenwald Faserplattenwerk GmbH
 Dr.-F.-A.-Freundt-Straße 3 | 63916 Amorbach
 tel +49 93 73.2 01-0 | info@owa.de
 www.owa-ceilings.com