

## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

---

### Soudal Soudafill

---

Revision: 26/04/2016

Page 1 from 3

Reference nr DOP: 231045

Unique identification code of the product type:

**Soudal Soudafill**

Intended use or uses of the construction product:

**Sealant for facade for interior and exterior application.**

Construction product in accordance with applicable harmonised specifications:

**EN 15651-1:2012: Type F - EXT-INT: CLASS 12.5P**

System or systems of assesment and verification of consistency of performance of the construction product, as set out in Annex V:

**System 3: for essential characteristics**

**System 3: for reaction to fire**

Name and contact address of the manufacturer as required pursuant to Article 11(5):

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

The notified body:

**IFT Rosenheim GmbH, NB 0757 has carried out Determination of the Product Type under system 3.**

## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

### Soudal Soudafill

Revision: 26/04/2016

Page 2 from 3

Declared Performance: EN 15651-1:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 25%	
Elastic recovery	< 40%	
Secant modulus at -30°C (N/mm <sup>2</sup> )	NPD	
Tensile properties at maintained extension at -30°C	NPD	
Adhesion-Cohesion at constant temperature	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 100%	
Tensile properties at break after water immersion	≥ 100%	
Durability	Pass	

**Conditioning:**

Method A

**Test substrate:**

Aluminium

Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Eric van Spreuwel

Technical Product Manager  
BE-2300 Turnhout, 26/04/2016

## CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 26/04/2016

Page 3 from 3



NB 0757

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr DOP: 231045

EN 15651-1: 2012

Sealant for facade for interior and exterior application.

### Soudal Soudafill

EN 15651-1:2012: Type F - EXT-INT: CLASS 12.5P

**Conditioning:**  
Method A  
**Substrate:**  
Aluminium  
Mortar

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 25%	
Elastic recovery	< 40%	
Secant modulus at -30°C (N/mm <sup>2</sup> )	NPD	
Tensile properties at maintained extension at -30°C	NPD	
Adhesion-Cohesion at constant temperature	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 100%	
Tensile properties at break after water immersion	≥ 100%	
Durability	Pass	