

## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

---

### Soudal Silirub Cleanroom

---

Revision: 23/04/2016

Page 1 from 4

Reference nr DOP: 230007

Unique identification code of the product type:

**Soudal Silirub Cleanroom**

Intended use or uses of the construction product:

**Sealant for facade for interior and exterior application, intended for use in cold climate.  
Sealants used for sanitary applications.**

Construction product in accordance with applicable harmonised specifications:

**EN 15651-1:2012: Type F - EXT-INT-CC: CLASS 25LM**

**EN 15651-3:2012: Type S: CLASS XS1**

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

**System 3: for essential characteristics**

**System 3: for reaction to fire**

Name and contact address of the manufacturer as required pursuant to Article 11(5):

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

The notified body:

**IFT Rosenheim GmbH, NB 0757 has carried out Determination of the Product Type under system 3.**

## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

### Soudal Silirub Cleanroom

Revision: 23/04/2016

Page 2 from 4

Declared Performance: EN 15651-1:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Elastic recovery	≥ 70%	
Secant modulus at 23°C (N/mm <sup>2</sup> )	≤ 0.4	
Secant modulus at -20°C (N/mm <sup>2</sup> )	≤ 0.6	
Secant modulus at -30°C (N/mm <sup>2</sup> )	≤ 0.9	
Tensile properties at maintained extension	NF	
Tensile properties at maintained extension at -30°C	NF	
Adhesion/cohesion at variable temperatures	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 25%	
Durability	Pass	

**Conditioning:**

Method A

**Test substrate:**

Aluminium

Mortar

Declared Performance: EN 15651-3:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Tensile properties at maintained extension	NF	
Adhesion/cohesion at variable temperatures	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Microbiological growth	0	
Durability	Pass	

**Conditioning:**

Method A

**Test substrate:**

Aluminium

## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

---

### Soudal Silirub Cleanroom

---

Revision: 23/04/2016

Page 3 from 4

Glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager  
BE-2300 Turnhout, 23/04/2016

## CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 23/04/2016

Page 4 from 4



NB 0757

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

14

Reference nr DOP: 230007

EN 15651-1: 2012

EN 15651-3: 2012

Sealant for facade for interior and exterior application, intended for use in cold climate.  
Sealants used for sanitary applications.

### **Soudal Silirub Cleanroom**

EN 15651-1:2012: Type F - EXT-INT-CC: CLASS 25LM

EN 15651-3:2012: Type S: CLASS XS1

**Conditioning:**

Method A

**Substrate:**

Aluminium

Mortar

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012 EN 15651-3: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Elastic recovery	≥ 70%	
Secant modulus at 23°C (N/mm <sup>2</sup> )	≤ 0.4	
Secant modulus at -20°C (N/mm <sup>2</sup> )	≤ 0.6	
Secant modulus at -30°C (N/mm <sup>2</sup> )	≤ 0.9	
Tensile properties at maintained extension	NF	
Tensile properties at maintained extension at -30°C	NF	
Adhesion/cohesion at variable temperatures	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 25%	
Microbiological growth	0	
Durability	Pass	